

ZRM 2.5-ES/CT

Lampen	35W	70W	100W	150W	250W
HI/MBI	●	●	●	●	●
HS/SON*		●	●	●	●

*HS 4-5KVp only

Type		ZRM 2.5-ES/CT
Article number		144185
Rated voltage	V	220-240
Permitted input voltage	V	202.4-264
Mains frequency	Hz	50-60
Ignition voltage	kV	4.0-5.0
Lamp wattage HS	W	70-250*
Lamp wattage HI	W	35-250
Temperature rise at IB = 0.54A (35W)	K	0.1
IB = 1.0A (70W)	K	2.5
IB = 1.2A (100W)	K	4
IB = 1.8A (150W)	K	9.5
IB = 3.0A (250W)	K	27
Losses at IB = 0.54A (35W)	W	~0.06
IB = 1.0A (70W)	W	~0.21
IB = 1.2A (100W)	W	~0.31
IB = 1.8A (150W)	W	~0.72
IB = 3.0A (250W)	W	~2.10
Max. cable capacitance	pF	100
Max. distance from lamp	m	1.5
Max. housing temperature tc	°C	105
Min. operating temperature	°C	-30
Timer cut out	sec.	1220 ±5%
3 stage counter	yes	
tunnel reset after	h	1
cold start sequence	min.	3
HI/HS pulse break timer	yes	
Weight	kg	0.13

