

# HXP R 206 W/45C

HXP | Mercury short-arc lamps, long life



#### Product family benefits

- Very high luminance
- Elliptical reflector for efficient focusing of the light
- Long lamp life

#### Product family features

- AC operation with square-wave current







# Product datasheet

#### Technical data

#### **Electrical data**


Lamp wattage	5500 W
Nominal voltage	85.0 V
Lamp voltage	4885 V <sup>1)</sup>
Lamp current	3.4 A
Type of current	AC
Nominal wattage	200.00 W

<sup>1)</sup> Initial voltage range

## Light technical data

Focal length	45.0 mm

## Dimensions & weight



Diameter	67.0 mm	
Length with base excl. base pins/connection	77.00 mm	

## Lifespan

1.00	4000 !
Lifespan	1000 h
•	

## Additional product data

Product remark	To be operated with PT-VIP 4AC/380 O3 DIM 206 VS50
----------------	--

## **Capabilities**

Cooling	Forced
Burning position	p20
Application	Other

#### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure in the hot state HXP lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321331472	HXP R 206 W/45C	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm <sup>3</sup>	158.00 g
4008321331489	HXP R 206 W/45C	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm <sup>3</sup>	363.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.