


LIGHTsignal HAL BEACON LIGHT

Warning and safety lights



360° rotating beacon light

Improved visibility and therefore increased safety for you and others



24V compatible

The beacon is suitable for 24V vehicles and due to the robust and functional design the beacon offers different application possibilities and a high flexibility.



Protection class: IP65

The OSRAM LIGHTsignal HAL has been tested in our DIN EN ISO/IEC 17025 certified environmental simulation laboratory for extreme external influences in terms of water, dust, heat and cold and validated with the protection class IP65



ECE Certified - ECE R65 & ECE R10

The required tests and approvals have been carried out and an ECE type approval has been granted1)



Light is safety- See and be seen with OSRAM

The OSRAM LIGHTsignal HAL BEACON LIGHT is a 360° rotating yellow beacon light that can be mounted on vehicles with unusual width, length or load, as well as on municipal vehicles, emergency, command and accident relief vehicles to draw attention to an unusual situation on the road or in the working environment. The rotating beacon from OSRAM can be used for better visual recognition, marking and securing of danger spots or special locations. Furthermore, rotating beacons are used in certain facilities, on machines and devices as well as in alarm systems. The rotating beacon from OSRAM is characterized by a high efficiency due to a high-quality H1 halogen lamp with up to 1900 lumens and 2200 Kelvin and thus ensures improved visibility and therefore increased safety for you and others - during the day and at night. Thanks to its non-slip, shock-absorbing rubber base, the warning light from OSRAM is particularly resistant to vibration. At the same time, the fully rubberized base contributes as a seal between the product and the underground. To reduce and prevent dirt from accumulating on the beacon, the OSRAM LIGHTsignal HAL uses a smooth surface on the housing, thus preventing the signal effect from being impaired by dirt. The OSRAM LIGHTsignal HAL BEACON LIGHT convinces by a high luminosity. With the help of a special texture inside the housing and through the highly polished parabolic reflector, an efficient and effective light output is generated. The beacon is suitable for 24V vehicles and due to the robust and functional design the beacon offers different application possibilities and a high flexibility. The mounting material included in the scope of delivery allows a direct and accurate mounting and thus an immediate use of the beacons. The three-point mounting system allows the beacon to be securely and firmly mounted on the vehicle roof. In addition, the LIGHTsignal HAL beacon light from OSRAM complies with the ECE R10 and R65 directives and is therefore approved for use in road traffic¹⁾ The OSRAM LIGHTsignal has been tested in our DIN EN ISO/IEC 17025 certified environmental simulation laboratory for extreme external influences in terms of water, dust, heat and cold and has been validated with IP protection class IP65.. OSRAM grants 2 years guarantee on this product²⁾Special regulations apply regarding the use and application of rotating beacons. This is regulated in the respective, country-specific road traffic licensing regulations.

Produktdatablad

Tekniska data

Produktinformation

Ordernummer	RBL101
Tillämpning (kategori- och produktspec.)	Warning and safety lights


Elektriska data

Nominell watttal	70,00 W
Nominell märkspänning	24,0 V

Fotometrisk data

Färgtemperatur	2200 K
Ljusfärg LED	Amber

Mått



produktvikt	653,00 g
Längd	150,0 mm
Höjd	193,0 mm

Livslängder

Garanti	2 years
---------	---------

Användningsområden

Teknologi	Halogen
-----------	---------

Certifikat och Standarder

Skyddstyp	IP65
-----------	------

Landspecifika kategorier

Produktdatablad




Ordernummer	RBL101
-------------	--------

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172192828	LIGHTsignal HAL BEACON LIGHT	Kapsel 1	155 mm x 155 mm x 235 mm	5.65 dm ³	746.00 g
4062172192835	LIGHTsignal HAL BEACON LIGHT	Transportförpackning g 12	495 mm x 340 mm x 498 mm	83.81 dm ³	9552.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Download

Dokument	
	User instruction LIGHTsignal HAL
	instruktionsfilm LIGHTsignal HAL (EN)
	Video OSRAM LIGHTsignal HAL Beacon Light (EN)

Lagliga hänvisningar

1) The OSRAM LIGHTsignal HAL BEACON LIGHT is approved according to ECE regulations and may therefore be installed and operated on public roads. In addition to the ECE approval of the product, individual special regulations and laws of the countries must be observed. Please note: Special regulations apply regarding the use and application of rotating beacons. This is regulated in the respective, country-specific road traffic licensing regulations. 2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.

OSRAM