



# Neptune 003 - half cover LED



Neptune - a robust and vandal resistant IP65 fitting with LED and sensor

## Description

Neptune 003 is a quality fitting in a quadratic shape (003) made of high pressure die-cast aluminium. Diffuser in UV- and vandal resistant polycarbonate. The front ring is fixed with 4 torx screws in stainless steel which are given a Delta seal treatment. IP65 class I.

## Application areas

P-house, facades, entrances, stairs, pedestrian areas, underpasses and tunnels.

## Mounting

Direct in ceiling or on wall.

## Installation

The fitting is prepared both for open and hidden installation. Push in terminal block 3x2x2,5 mm<sup>2</sup> with through-wiring possibilities.

## LED module

Colour temperature 3000K - 4000K  
 Effect fitting 12W  
 Luminous flux fitting 222 lm  
 Lifetime L70B50 50.000 t

## Additional

The sensibility is adjusted on the microwave sensor. Likewise the hold time (exposure time after detected movement) might be adjusted (5 sek - 25 min). The sensor has also a setting for a twilight function (2 - 30 lux). Radar can also be used as Master for other fittings.

White	Black	Type	Decor	Light source
115067	115068	Neptune 003 LED	Half cover	LED 12W 840
118679	117729	Neptune 003 LED Radar	Half cover	LED 12W 840
119244	119243	Neptune 003 LED Radar MinMax	Half cover	LED 12W 840 + LED 1W E14
119238	116077	Neptune 003 LED	Half cover	LED 12W 830
119240	119239	Neptune 003 LED Radar	Half cover	LED 12W 830
119242	119241	Neptune 003 LED Radar MinMax	Half cover	LED 12W 830 + LED 1W E14

### NB!

A microwave sensor detect all forms of movement, not only from people and animals.

This means that the sensor might detect movements for instance from branches or leaves.

Please allow for this when installing the fitting to avoid unwanted functions.

Reservation for misprinting or product changes.