



Protect - a robust and vandal resistant IP65 fitting with LED and sensor

Description

Protect 002 is a quality fitting in a oval shape (002) made of high pressure die-cast aluminium. Diffuser in UV- and vandal resistant polycarbonate. The front ring is fixed with 4 torx screws in stainless steel which are given a Delta seal treatment. IP65 class I.

Application areas

P-house, facades, entrances, stairs, pedestrian areas, underpasses and tunnels.

Mounting

Direct in ceiling or on wall.

Installation

The fitting is prepared both for open and hidden installation. Push in terminal block 3x2x2,5 mm² with through-wiring possibilities.

LED module

Colour temperature 3000K - 4000K
 Effect fitting 12W
 Luminous flux fitting 505 lm
 Lifetime L70B50 50.000 t

Additional

The sensibility is adjusted on the microwave sensor. Likewise the hold time (exposure time after detected movement) might be adjusted (5 sek - 25 min). The sensor has also a setting for a twilight function (2 - 30 lux). Radar can also be used as Master for other fittings.

White	Black	Type	Light source
111876	111242	Protect 002 LED	LED 12W 840
111888	111889	Protect 002 LED Radar	LED 12W 840
119249	119248	Protect 002 LED Radar MinMax	LED 12W 840 + LED 1W E14
111241	111242	Protect 002 LED	LED 12W 830
111886	111887	Protect 002 LED Radar	LED 12W 830
	119247	Protect 002 LED Radar MinMax	LED 12W 830 + LED 1W E14

NB!

A microwave sensor detect all forms of movement, not only from people and animals.

This means that the sensor might detect movements for instance from branches or leaves.

Please allow for this when installing the fitting to avoid unwanted functions.

Reservation for misprinting or product changes.