



Technical Data

| Category | Article number | Description |
|----------|----------------|------------------------|
| Dimmer | 2490HP | Led Tronic Wall Dimmer |

| Input/ Output | |
|--------------------------------|-----------|
| Rated voltage | 230V |
| Tolerance of the input voltage | +/-10% |
| Input frequency | 50Hz |
| Input current | 1.5A max. |
| Rated power | 150W/VA |
| Rated power LED | 70W |
| Minimal load for lighting | 5W *) |
| Power consumption | 1W |

| Function | |
|--------------------------|-----------------------------|
| Overload protection | Thermal fuse 125C |
| Short-circuit protection | Electronic |
| Dimming range | 10 - 100% |
| Time for start-up | ~ 1 sec |
| Features | LED indicator 8 profiles |

| Shape | |
|----------------|------------------------------------|
| Dimension (mm) | 70 x 70 x 32 |
| Weight (g) | 60g |
| Switch | Mechanical push button alternating |
| Artwork | Tradim logo |
| Shaft version | 4mm shaft metal 6mm adapter |

| Safety approval | |
|-----------------|--|
| CE/ KEMA Keur | |

| Remarks | |
|---|--|
| Lamp can be switched off 100% due to press/turn switch | |
| Wall dimmer 2490HP has 8 dimming profiles which can be chosen by small switch on dimmer. Led indicator on dimmer shows the profile (profile 3 has 3 times led on/off, than pause, again 3 times led on/off) | |

*) Lower power of led lamps by experiment possible